

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Product name: LIQUID ULTIMATE MASTER  
Product code: T/LUM

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use of substance / mixture: Cleaning agent for carpets and upholstery.

**1.3. Details of the supplier of the safety data sheet**

Company name: Alltec Network Ltd  
Butts Business Centre  
Fowlmere, Royston  
Hertfordshire  
SG8 7SL  
United Kingdom  
Tel: 01763208222  
Fax: 01763208906  
Email: [info@alltec.co.uk](mailto:info@alltec.co.uk)

**1.4. Emergency telephone number**

Emergency tel: 01763208222  
(office hours only)

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

Classification under CLP: Eye Dam. 1: H318; Aquatic Chronic 3: H412; Skin Sens. 1: H317

Most important adverse effects: May cause an allergic skin reaction. Causes serious eye damage. Harmful to aquatic life with long lasting effects.

**2.2. Label elements**

Label elements:

Hazard statements: H317: May cause an allergic skin reaction.  
H318: Causes serious eye damage.  
H412: Harmful to aquatic life with long lasting effects.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion  
GHS07: Exclamation mark



Precautionary statements: P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P302+352: IF ON SKIN: Wash with plenty of water/.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310: Immediately call a POISON CENTER/doctor/if you feel unwell or if irritation persists.  
P321: Specific treatment (see instructions on this label).

# SAFETY DATA SHEET

LIQUID ULTIMATE MASTER

Page: 2

## 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### NEODOL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	68131-39-5	-	Skin Irrit. 2: H315; Eye Dam. 1: H318; Aquatic Acute 1: H400; Aquatic Chronic 3: H412	1-10%

##### TKPP

-	7320-34-5	-	Eye Irrit. 2: H319	1-10%
---	-----------	---	--------------------	-------

##### ETHANOL

200-578-6	64-17-5	Substance with a Community workplace exposure limit.	Flam. Liq. 2: H225	1-10%
-----------	---------	--	--------------------	-------

##### FLORAL FRAGRANCE

-	-	-	Skin Sens. 1: H317; Aquatic Chronic 2: H411; Eye Irrit. 2: H319	1-10%
---	---	---	---	-------

##### METHANOL

200-659-6	67-56-1	-	Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370	<1%
-----------	---------	---	---	-----

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Delayed effects can be expected after long-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Not applicable.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

[cont...]

# SAFETY DATA SHEET

LIQUID ULTIMATE MASTER

Page: 3

## 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Do not attempt to take action without suitable protective clothing - see section 8 of SDS.  
Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**ETHANOL**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1920 mg/m <sup>3</sup>	-	-	-

**METHANOL**

UK	266 mg/m <sup>3</sup>	333 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Impermeable gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

## Section 9: Physical and chemical properties

[cont...]

# SAFETY DATA SHEET

LIQUID ULTIMATE MASTER

Page: 4

## 9.1. Information on basic physical and chemical properties

State: Liquid  
Colour: Milky white  
Odour: Pleasant  
Viscosity: Non-viscous  
pH: 9.5

## 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

Conditions to avoid: Heat.

### 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

Hazardous ingredients:

#### ETHANOL

IVN	RAT	LD50	1440	mg/kg
ORL	MUS	LD50	3450	mg/kg
ORL	RAT	LD50	7060	mg/kg

#### METHANOL

IVN	RAT	LD50	2131	mg/kg
ORL	MUS	LD50	7300	mg/kg
ORL	RAT	LD50	5628	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

### Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

[cont...]

# SAFETY DATA SHEET

LIQUID ULTIMATE MASTER

Page: 5

**Inhalation:** Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Delayed effects can be expected after long-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

**Transport class:** This product does not require a classification for transport.

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H225: Highly flammable liquid and vapour.

H301: Toxic if swallowed.

H311: Toxic in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H370: Causes damage to organs <or state all organs affected, if known> <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H400: Very toxic to aquatic life.

[cont...]

**SAFETY DATA SHEET**  
LIQUID ULTIMATE MASTER

Page: 6

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.