

MSDS

SAFETY DATA SHEET



Heavy Duty Extreme

Code: Cleaner Number 3

Page: 1

Compilation date: 17.10.12

Revision No: 6

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: HEAVY DUTY EXTREME

Product code: Cleaner No 1

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: The Tile Master Global Ltd

22 Village Square,

Bramhall Centre,

Stockport,

Cheshire,

SK7 1AW

Tel: +44 0800 059 9206

Email: sales@thetilemaster.co.uk

1.4. Emergency telephone number

Tel: +44 0800 059 9206

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: Xi: R38; Xi: R41

Most important adverse effects: Irritating to skin. Risk of serious damage to eyes.

2.2. Label elements

Label elements under CHIP:

Hazard symbols: Irritant.

Risk phrases: R38: Irritating to skin.

R41: Risk of serious damage to eyes.

Safety phrases: S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S39: Wear eye / face protection.

[cont...]

The Tile Master Global Ltd

22 Village Square, Bramhall Centre Stockport, Cheshire, SK7 1AW

Tel No: 0800 059 9206 www.thetilemaster.co.uk

SAFETY DATA SHEET

HEAVY DUTY EXTREME - Cleaner No 3

Page: 2

2.3. Other hazards

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

DISODIUM METASILICATE

EINECS CAS CHIP Classification CLP Classification Percent

229-912-9 6834-92-0 C: R34; Xi: R37 Skin Corr. 1B: H314; STOT SE 3:

H335

1-10%

2-(2-BUTOXYETHOXY)ETHANOL

203-961-6 112-34-5 Xi: R36 Eye Irrit. 2: H319 1-10%

2-BUTOXYETHANOL

203-905-0 111-76-2 Xn: R20/21/22; Xi: R36/38 Acute Tox. 4: H332; Acute Tox. 4:

H312; Acute Tox. 4: H302; Eye Irrit. 2:

H319; Skin Irrit. 2: H315

1-10%

PRIMARY ALCOHOL ETHOXYLATE

- 68439-45-2 Xn: R22; Xi: R41 - 1-10%

02845000

- 1300-72-7 Xi: R36 - 1-10%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

[cont...]

The Tile Master Global Ltd

22 Village Square, Bramhall Centre Stockport, Cheshire, SK7 1AW

Tel No: 0800 059 9206 www.thetilemaster.co.uk

SAFETY DATA SHEET

HEAVY DUTY EXTREME - Cleaner No 3

Page: 3

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

[cont...]

The Tile Master Global Ltd

22 Village Square, Bramhall Centre Stockport, Cheshire, SK7 1AW

Tel No: 0800 059 9206 www.thetilemaster.co.uk

SAFETY DATA SHEET

HEAVY DUTY EXTREME - Cleaner No 1

Page: 4

8.1. Control parameters

Hazardous ingredients:

2-(2-BUTOXYETHOXY)ETHANOL

Workplace exposure limits: Respirable dust

State 8 hour TWA 15 min. STEL 8 hour TWA 15 min. STEL

UK 67.5 mg/m³ 101.2 mg/m³ - -

2-BUTOXYETHANOL

UK 25 ppm 50 ppm - -

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Red

Odour: Characteristic odour

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Flash point°C: 70 **pH:** >12.5

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

[cont...]

The Tile Master Global Ltd

22 Village Square, Bramhall Centre Stockport, Cheshire, SK7 1AW

Tel No: 0800 059 9206 www.thetilemaster.co.uk

SAFETY DATA SHEET

HEAVY DUTY EXTREME - Cleaner No 3

Page: 5

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

DISODIUM METASILICATE

ORL MUS LD50 770 mg/kg

ORL RAT LD50 1153 mg/kg

2-(2-BUTOXYETHOXY)ETHANOL

ORL MUS LD50 6050 mg/kg

ORL RAT LD50 4500 mg/kg

2-BUTOXYETHANOL

IVN RAT LD50 307 mg/kg

ORL MUS LD50 1230 mg/kg

ORL RAT LD50 470 mg/kg

PRIMARY ALCOHOL ETHOXYLATE

ORL RAT LD50 >200<2000 mg/kg

02845000

O -RL R -AT L -D50 >700 0- m -g/kg

Relevant effects for mixture:

Effect Route Basis

Irritation OPT DRM Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

[cont...]

The Tile Master Global Ltd

22 Village Square, Bramhall Centre Stockport, Cheshire, SK7 1AW

Tel No: 0800 059 9206 www.thetilemaster.co.uk

SAFETY DATA SHEET

HEAVY DUTY EXTREME - Cleaner No 3

Page: 6

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: The surfactants in this product comply with the biodegradability criteria as laid down in

Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them at their direct request or at the request of the detergent manufacturer.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1760

14.2. UN proper shipping name

Shipping name: CORROSIVE LIQUID, N.O.S.
(DISODIUM METASILICATE)

14.3. Transport hazard class(es)

Transport class: 8

[cont...]

The Tile Master Global Ltd

22 Village Square, Bramhall Centre Stockport, Cheshire, SK7 1AW

Tel No: 0800 059 9206 www.thetilemaster.co.uk

SAFETY DATA SHEET

HEAVY DUTY EXTREME - Cleaner No 3

Page: 7

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H314: Causes severe skin burns and eye damage.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.

R22: Harmful if swallowed.

R34: Causes burns.

R36/38: Irritating to eyes and skin.

R36: Irritating to eyes.

R37: Irritating to respiratory system.

R38: Irritating to skin.

R41: Risk of serious damage to eyes.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[final page]

The Tile Master Global Ltd

22 Village Square, Bramhall Centre Stockport, Cheshire, SK7 1AW

Tel No: 0800 059 9206 www.thetilemaster.co.uk