SAFETY DATA SHEETS TileMaster – Rust Away

Section 1 – Product Identification	
Product name	TileMaster Rust Away
Product type Master	Liquid
Product description	Water-based solution to clean rust from stone
Prepared by	TileMaster Global Limited, Unit 11 / 12 Shepley
	Land Ind Est, Hawk Green, Stockport, SK6 7JW
	Tel: 0161 444 0377 email:
	info@thetilemaster.co
Compilation date	18.10.2017 – Revision No.2

Section 2 – Hazards Identification

2.1

Classification of the substance according to Regulation EC n. 1272/2008

The product is not classified as dangerous -

Skin Corr. 1A: H314

Causes severe skin burns and eye damage

2.2

Label indications:

H314 causes severe skin burns and eye damage

GHS05: Corrosion



2.3

Hazards:

GHS05: Corrosion

This product is not identified as a PBT/vPvB substance

2.4

Precautionary statements:

P264: Wash hand thoroughly after handling P280: Wear protective gloves/eye protection

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing

P405: Store locked up.

Section 3 – Composition / Information on the ingredients

3.1

Substances:

Name	EINECS	CAS	CHIP	CLP Classification	Percen
			Classifi		t
			cation		
ORTHOPHOSPHORIC ACID	231-633-2	7664-38-2	-	Skin Corr. 1B: H314	10-12%

Section 4 – First Aid Measures

4.1

First aid measured description:

In case of contact with the skin: Wash the area with soap and water, remove dirty shoes and clothes if contact via area. Consult a doctor in case of irritation, swelling or redness persist. In case of contact with the eyes: bathe and rinse well with water for 15 minutes.

4.2

Main symptoms and effects both acute and delayed, see chapter 11:

Skin contact: Redness, irritations Eyes contact: Eyes irritation

Ingestion: There may be irritation of the throat

Inhalation: No symptoms.

4.3

Indication on the eventual necessity of contacting a doctor and special treatments - Follow doctor's instructions.

Section 5 – Anti-Fire Measures

5.1

The product is not flammable

5.2

Exposure hazards: In combustion emits toxic fumes

Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6 – Accidental Release Measures

6.1

Personal equipment, protective clothing and emergency procedures:

Wear suitable protective clothes

6.2

Precautions for the environment:

Do not pour down drains

6.3

Methods and materials to collect and clean:

Collect with absorbent materials like sand, sawdust and dispose according to proper rules

Section 7 – Handling and Storage

7.1

Precautions for safe handle:

Wear gloves, apron, mask and boots.

7.2

Safe warehouse:

Keep container well sealed in a dry place; protect from freeze and avoid temperatures higher than 40°C. Do not keep in warehouse together with acids and strong basis.

Section 8 – Exposure Control and Protection

8.1

Since the use of suitable technical measures should be first than personal protection equipment, it's necessary to ensure a proper ventilation through the use of a good aspiration device or the polluted air discharge. If these operations do not keep product concentration under minimum exposure values, it will be necessary to wear a suitable breathing apparatus protection. During use, refer to danger label for more details. Personal protective clothes must be in compliance with the rules here below indicated:

Hands Protection

Protect hands using working gloves, II category. (ref. Directive 89/686/CEE and Rule EN 374) like: PVC, neoprene, nitrile or equivalent.

The final choice of the gloves must consider: degradation, breaking time and permeability. In case of mixtures the gloves resistance must be checked before using, it is not foreseeable. Gloves have a wear and tear term that depends on exposure time.

Eyes Protection Wear sealing protective mask (ref. Rule EN 166)

Skin Protection Wear long sleeves working clothes and shoes for professional use, II category. (ref. Directive CEE and EN 344 rule). Wash with plenty of water after taking protective clothes off. Breathing Protection

In case of overcoming of the limit value of one or more substances present in the product, wear a mask with filter A type or the universal type, whose class (1,2 or 3) will be chosen according to the use. (ref. EN 141 Rule). The use of breathing apparatus protections, like mask with filter for organic vapors and powders/fog, it's compulsory in absence of technical measures to limit the worker exposure. The protection given by the mask is limited anyway. If the substance is odourless or in case of emergency (unknown time of exposure or the oxygen level in the ambient is lower than 17%) wear a compressed air auto-breather at open circuit (ref. Rule EN 137) or a respirator with external air outlet for the use with whole mask, semi-mask or nozzle. (Ref. Rule EN 138). If there's the risk to get squirts or sprinkles due to the type of work performed, it's necessary to foresee a suitable mucous protection (mouth, nose, eyes) in order to avoid accidental absorptions.

8.2

Limits of exposure:

No substance at exposure limit

8.3

Exposure control, Technical controls:

Handle in well ventilated areas

Tile Master Global Ltd Unit 11 / 12 Shepley Road Ind Est E info@thetilemaster.co.uk Hawk Green, Marple, Stockport, SK6 7JW

T +44 (0)161 444 0377 www.thetilemaster.co.uk

8.4

Individual protection:

Wear gloves and mask, in normal use conditions no vapors is generated

8.5

Environmental protection:

Avoid discharge in sewers

Name	State	8 Hour TWA	15 Min. Stel	8 Hour TWA	15 min.
					STEL
ORTHOPHOSPHORIC	UK	1 mg/m3	2 mg/m3	-	-
ACID100%					

Section 9 – Chemical and Physical Propoerties

α		1	
J	•	1	

Status:

Liquid

Color:

Clear

Odor:

Characteristic odour

Smelling threshold:

Non-oxidising (by EC criteria)

pH:

<2

Boiling point:

100°C approx.

Fusion point:

ND

Flashing point:

70°C

Ignition temperature:

not determined

Vapors:

Not determined

Viscosity:

Non-Viscous

Solubility:

Soluble

Section 10 - Stability and Reactivity

10.1

Reactivity:

No dangerous reaction in normal conditions of use

10.2

Chemical stability:

The product is stable

10.3

Possible dangerous reactions:

No dangerous reactions detected

10.4

Conditions to avoid:

Heat

10.5

Hazardous decomposition products:

Decomposition starts at temperatures higher than 150°C; in normal use conditions no decomposition is detected

Section 11 - Toxicological Infomation

ORTHOPHOSPHORIC ACID100%	ORL	RAT	LD50	1530	Mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Contact with the skin:

May cause irritation and redness

Contact with the eyes:

May be pain and redness, eyes may water profusely. There may be severe

pain with vision becoming blurred. May cause permanent damage.

Ingestion:

May cause irritation to throat, nausea and stomach pain may occur

Inhalation:

May be irritation of the throat with a feeling of tightness in the chest

Section 12 – Ecological Information

There's no information on the product, so use it according to good working procedures, do not waste it in the environment. Absolutely avoid to waste product in the ground or drains. Call authorized companies if the product reaches water drains or in case of ground or flora pollution. Follow all the measures to reduce at the minimum level the effects on water drains.

12.1

Toxicity Information:

No data vailable

12.2

Persistence and degradability Information:

The surfactants in this product comply with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the component authorities of the Member States and will be made available to them at their direct request or

at the request of the detergent manufacturer.

12.3

Potential bio-accumulative Information:

No bioaccumulation potential

12.4

Mobility in the ground Information:

Readily absorbed into soil.

12.5

Results of the PBT and vPvB evaluation Information:

This product is not identified as a PBT/vPvB substance

12.6

Additional effects Information:

Negligible ecotoxicity

Section 13 – Disposal Considerations

13.1

Waste Handling:

Re-use, if possible the product. Product residues must be regarded as special dangerous waste. Waste danger that contain this product must be evaluated on the basis of current rules.

Disposal:

Must be performed by company authorized to waste handling, according to national and local current rules. Polluted Packages, Polluted packages must be recovered or wasted in compliance with National rules concerning waste management.

Section 14 - Transport

UN Number:

UN1805. Phosporic Acid, Liquid, Class 8, Packing III,

Section 15 – Regulatory Information

Substances SVHC: none Annex XVII: none

Section 16 – Other Information

16.1

This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010 Hazard indications:

Flam. Liq.2 Flammable liquid, cat. 2

Acute tox.3 High toxicity, cat. 3

STOT SE 1 Specific toxicity for target - single exposure, Cat. 1

Flam.Liq.3 Flammable liquid, cat.3

STOT SE 3 Specific toxicity for target-single exposure, Cat.3

Carc. 1B Cancerougenicity, CAT 1 B

Muta, 1B Mutagenicity on stem cells, cat. 1 B

Asp. Tox.1 Danger in case of aspiration, cat. 1

Acute tox.4 High toxicity, cat. 4

STOT RE 1 Specific toxicity for target - repeated exposure, cat. 1

Eye Irrit. 2 Eyes irritation, cat.2

Aquatic Acute 1 Dangerous for fish fauna, high toxicity, cat.1

Aquatic Chronic 1 Dangerous for fish fauna, high toxicity, cat.1

H302 harmful if swallowed

H314 causes severe skin burns and eye damage.

H315 causes skin irritation

H318 causes serious eve damage

H319 Causes eye irritation

H332 harmful if inhaled

H335 may cause respiratory irritation

R10 flammable

R11 easily flammable

R 23/24/25 toxic by inhalation, skin contact, ingestion

R36 eyes irritating

R48/25 toxic: serious healthy damages in

Case of long exposure by ingestion.

R50/53 high toxic for aquatic organism,

At long term it may cause negative effects for fish fauna

R65 harmful: if swallowed could cause serious damage to lungs.

R66 continuous exposure may cause skin dryness and cracks.

R67 vapours inhalation may cause sleepiness and giddiness.

R68 possibility of non-reversible effects.

General Bibliography

- 1. Directive 1999/45/CE and following modifications
- 2. Directive 67/548/CEE and following modifications
- 3. Regulation (CE) 1907/2006 of European Parliament (REACH)
- 4. Regulation (CE) 790/2009 of European Parliament (I Atp. CLP)
- 5. Regulation (CE) 453/2010 of European Parliament
- 6. The Merck Index Ed. 10
- 7. Handling Chemical Safety
- 8. Niosh- Regestry of Toxic Effects of Chemicals Substances
- 9. INRS Fiche Toxicologique
- 10. Patty- Industrial Hygiene and Toxicology
- 11. N.I. Sax. Dangerous properties of Industrial Materials 7 Ed. 1989

USER'S NOTES:

The information herein contained have been draught on the basis of available knowledge upon data sheet version. The user must make sure of the suitability and completeness of the information referring to the specific use of the product. Do not read this document as warranty of any specific property of the product. Since the use of the product is not under our direct control, it's the user's liability respect current rules in terms of hygiene and safety. We are not held liable for un-proper use.